



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 158(3) EPC

(43) Date of publication:
27.03.2002 Bulletin 2002/13

(51) Int Cl.7: **B65G 69/18, B60P 3/16**

(21) Application number: **01905839.5**

(86) International application number:
PCT/ES01/00072

(22) Date of filing: **23.02.2001**

(87) International publication number:
WO 01/64558 (07.09.2001 Gazette 2001/36)

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Espina Frutos, Juan José**
35118 Arinaga (ES)

(30) Priority: **01.03.2000 ES 200000498**

(74) Representative: **Alvarez, Fernando**
Nunez de Balboa, 31,
P.O. Box 170
28001 Madrid (ES)

(71) Applicant: **Espina Frutos, Juan José**
35118 Arinaga (ES)

(54) **DEVICE FOR CAPTURING DUST IN THE LOADING OF CONCRETE MIXER TRUCKS**

(57) The device comprises a receptacle (1) with a mouth (4') to which the end of the duct through which the concrete falls into the tank (3) of a concrete mixer tank is coupled; said receptacle is fixed and it is provided with a gap (6) for adapting the rear part of said tank (3), in order to retain the dust originated by the fall of the concrete inside said receptacle (1); a part of said dust is released through the duct (9) towards a common col-

lector (10) while the other part is suctioned through a vacuum head (2) made of a frusto-conical body the great base of which is coupled to the loading mouthpiece (3') of the tank (3), and the small base of which leads to a duct (13) ending in the common collector (10), from which the dust is suctioned and conveyed through a recipient or hopper (22) having filters, in order to clean it and gather it definitively in a recipient or common collector (20).




FIG.1




FIG. 3

Description

OBJECT OF THE INVENTION

[0001] The present invention refers to a device for collecting and removing the dust originated when loading the tank of a corresponding concrete mixer truck, and it is based on the provision of a fixed receptacle disposed between the concrete and the aggregates chute duct and the input mouthpiece of the corresponding concrete mixer tank, said receptacle being complemented with a vacuum head having a frusto-conical configuration, at one of which ends a mouth is established which can be disposed facing the mouthpiece of the concrete mixer tank, while a fan that is disposed in the smaller and back-side base of said vacuum head, in combination with an external vacuum system, for collecting the dust and bringing it on a recipient container; all this constitutes an assembly to which the backside of the truck has adapt by means of reversing the motion of the same.

[0002] The object of the invention is to avoid the release of the dust commonly produced when loading concrete, aggregates, sand, water, etc., into concrete mixer trucks.

BACKGROUND OF THE INVENTION

[0003] Normally, the loading of a concrete mixer truck is done by positioning the same in correspondence to a hopper or silo from which, and by means of the appropriate ducts, the correspondent dose of water, aggregate and concrete is conveyed to the concrete mixer tank; all this is complemented with the appropriate weighting and volume control means in order to dose the aggregates, the concrete and also the water.

[0004] The discharge of aggregates and concrete produces, logically, dust, due to their chute, by gravity, into the tank; said dust invades the environment, and this is problematic and inconvenient. The release of dust to the outside of the concrete mixer tank is usually produced by two main reasons, one of which is due to the fact that the air moved from the inside of the tank pushes, when moved, the fine particles of aggregates and concrete falling from the correspondent hopper or silo into the tank; the second reason is due to the fact that a big amount of dust is produced when the discharged material crashes into the truck collecting hopper, which means about 15% of the light particles.

[0005] There is a system to prevent the formation of dust or to prevent the release of dust to the outside, which is the same; said system consists in an expensive assembly mounted on the upper part of a ramp to which the correspondent concrete mixer truck can access, said concrete mixer truck being positioned under a stand having aggregate and concrete discharge means, all this in such a way that said stand has an aperture in one of its sides, more specifically the one facing the ramp; the vehicle, having appropriate means, is posi-

tioned under the stand, in correspondence with said aperture, preventing in this way the release of the dust.

[0006] The above-mentioned system is not completely efficient because there is always a substantial release of dust and there are other problems such as the complexity of the assembly, its static position and the gathering of dust at the level of the same loading area or platform where the vehicle or truck is located.

DESCRIPTION OF THE INVENTION

[0007] The device of the present invention is designed to solve these problems in a completely satisfactory manner, based on a solution which is both simple and efficient: the device comprises two basic elements, one is configured as an almost sealed receptacle and it is constituted from an horizontal plate having a coupling mouth adapted to the concrete and even aggregate chute duct, in such a way that a series of flaps made of rubber in combination with fabrics, are fixed to the perimetral and rectangular edge of said plate, defining the receptacle as such, characterised by the fact that one of the flaps has a gap with an arched configuration to allow the positioning of the concrete mixer tank, when the correspondent truck moves backwards on said receptacle. Furthermore, inside said receptacle a vacuum head is provided, movable along a forward and backward direction by means of a set of bearings disposed on guides, mounted in the lateral heel plates between which a mounting shaft of said vacuum head is disposed; said vacuum head comprises a frusto-conical body, pivotable in relation to said shaft in order to allow its coupling to the loading mouthpiece of the concrete mixer tank when the truck moves backwards, characterised specially in that the movement of said vacuum head prevents any damage or deterioration of the same because when the truck moves backwards the head can move on the guides mentioned above.

[0008] Both the receptacle first mentioned above and the vacuum head include corresponding ducts through which the air is suctioned to a common collector communicating to a sort of hopper by means of which, together with the appropriate filters, the dust is filtered and falls into a tank or collecting container, all this in combination with a motor driven fan.

[0009] In relation to the coupling of the vacuum head edge to the loading mouthpiece of the concrete mixer tank, a kind of perimetral and damping screen is provided, contributing to the fixing or coupling of said vacuum head edge to the mouthpiece of the tank, more particularly, on grooves provided on the back and lateral side of the mouthpiece of the tank.

[0010] By means of the above mentioned device, when the product (concrete) falls in the concrete mixer tank, the correspondent dust will be generated during the fall and will remain inside the receptacle, in order to be released through the duct leading to the general collector mentioned above, while the other big part of the

dust is suctioned by the vacuum head and reaches also the output collector trough the correspondent duct.

DESCRIPTION OF THE DRAWINGS

[0011] In order to complete the above description and to contribute to a better understanding of the features of the invention, according to a preferred practical embodiment of the same, a set of drawings is included as a part of said description. They are given for illustrative and not limitative purpose, in which:

Figure 1 shows a view according to a rear perspective of the device of the present invention when it is positioned on the rear part of the tank of a concrete mixer truck for collecting the dust produced when loading said tank,

Figure 2 shows another view according to a rear perspective representing the way in which the vacuum head is mounted on the correspondent rear part of the loading mouthpiece of the concrete mixer tank,

Figure 3 shows a perspective view of the dust collecting receptacle, on the gap of which, provided in one of its sides or flaps, the rear part of the tank of the truck is adapted, the discharge of concrete and even of the aggregates being produced through said receptacle. This figure shows also the vacuum head disposed inside said receptacle, which is complemented with a filter placed in its coupling mouth, on the loading mouthpiece of the concrete mixer tank,

Figure 4 shows, finally, a general perspective view of the vacuum head, a longitudinal part of which has been sectioned in order to show the situation of its fan.

PREFERRED EMBODIMENT OF THE INVENTION

[0012] As the above mentioned figures show, the device of the invention is constituted from two fundamental elements (1) and (2), the first of which is functioning as a receptacle for collecting the dust produced when loading the tank (3) of a concrete mixer truck, and the second of which is functioning as a vacuum head for suctioning said dust, and being located inside the first element.

[0013] The receptacle (1) is constituted from a preferably rectangular plate (4), on the perimeter of which a series of flaps (5) made of rubber or the like are conveniently fixed by means of screws or any other conventional means; said flaps define the receptacle as such, and said plate (4) is provided with an aperture or mouth (4') to which the lower end of a duct (7) through which the concrete and the aggregates fall when loading the concrete mixer tank (3), is coupled.

[0014] One of the flaps (5) delimiting the receptacle (1), and more concretely the one referenced as (5'), is provided with a large gap (6) with an arched configuration in order to adapt to the rear part of the tank (3) and to enable the product to access it during the loading operation, through the mouthpiece (3') of said tank (3).

[0015] The receptacle (1) is provided with an aperture in the flap opposed to the one mentioned above, to which a duct (9) flowing into a collector (10) is coupled by means of a fastener (8).

[0016] On the other hand, the vacuum head (2) of the present device determines an aspirator constituted from a frusto-conical body, as illustrated clearly in the figures, the great base of which determines a mouth (2') for coupling to the mouthpiece (3') of the tank (3); said mouth (2') is complemented with a perimetral and cushioned piece or body (11) in order to lie on the channels (12) established on the rear part of said concrete-mixer tank (3), more particularly in correspondence with the loading mouthpiece (3') of the same, in such a way that said perimetral and cushioned piece (11) cooperates in the coupling to said loading mouthpiece (3').

[0017] In correspondence with the end or small base of the frusto-conical body of the described head (2), an aspirator (12') is mounted, from which the frusto-conical body (2) extends forming a coupling to a duct (13) flowing into a common collector (10) mentioned above.

[0018] The general vacuum element or head (2) of the aspirator is pivotally mounted on a shaft (14) passing through two lateral and rear heel plates (15) of said frusto-conical body of the vacuum head and is supported between said lateral plates (16) carrying bearings or wheels (17) sliding on fixed guides (18), by means of which the movement of the vacuum head body (2) is enabled in the forward and backward direction, while the mounting shaft (14) allows it to pivot up and down in order to adapt and couple to the loading mouthpiece (3') of the tank (3). At the entrance (2') or base having the greatest diameter of the frusto-conical body of the head (2) a grid (19) is provided, supported on the same perimetral and cushioned piece (11), said grid (19) providing a higher speed to the suctioned air.

[0019] According to this configuration, the concrete-mixer truck must be positioned conveniently, in such a way that the loading mouthpiece (3') of the tank (3) of said concrete-mixer truck be located in correspondence to the receptacle (1); the rear part of said tank (3) adapts to the gap, having a bridge configuration (6), of said receptacle (1), while the mouth (2') of the frusto-conical body of the vacuum head results also facing the loading mouthpiece (3') of the tank (3) and the cushioned piece (11) lies on the lateral channels (12) to prevent the fall of the product out of the tank (3).

[0020] In this way, through the duct (7) that can be coupled to the mouth (4') of the receptacle (1), the concrete and even the aggregates are discharged into the tank (3), in such a way that the produced dust remains inside the receptacle (1) and part of it is released


through the duct (9), arriving in the common collector (10), and another part, through the vacuum set (2), arrives also in the collector (10) via the conduct (13), and from said collector to a hopper (22) in which the dust is filtered and falls into a recipient or gathering collector (20); the suction is made by means of a motor-driven fan (21), as illustrated in figure 1.

Claims

1. Device for collecting dust when loading concrete mixer trucks provided to be located and conveniently adapted to the rear part of the tank of a concrete mixer truck, in correspondence to the loading mouthpiece of the same, by means of the displacement of the latter in order to adapt to said device, **characterised by** the fact that it is constituted by means of two fundamental dust collecting elements the first of which being a receptacle (1) coupled to the bottom end of the duct (7) through which the concrete and even the aggregates enter into the tank (3) of the concrete mixer, said receptacle (1) having a gap (6) in one of its walls on which the rear part of the tank (3) of the mixer truck is adapted, while the second element is constituted by a vacuum head (2), located inside the receptacle (1), made by a frusto-conical body the great base of which defines a mouth (2') for coupling to the loading mouthpiece (3') of the tank (3) of the concrete mixer, while the small base comprises an aspirator (12') leading to a duct (13) through which it access a common collector (10), into which flows also a duct (9) coming from the receptacle (1) collecting the dust originated during the chute of the concrete from the duct (7) into the tank (3).
2. Device for collecting dust when loading concrete mixer trucks according to claim 1, **characterised by** the fact that the receptacle (1) is made from a rectangular plate (4) on which a series of flaps (5) made of rubber or a similar material, in combination with a fabric, are fixed, delimiting the periphery of said receptacle (1), one of said flaps (5') having a gap (6) forming an arch to adapt the rear part of the tank (3), while the opposed flap has an aperture for coupling, by means of a fastener (8), to the duct (9) releasing the dust to a common collector (10).
3. Device for collecting dust when loading concrete mixer trucks according to claim 1, **characterised by** the fact that the frusto-conical body of the vacuum head (2) is provided with heel plates (15); a shaft (14) passes through them and their ends are mounted between respective lateral plates (16) having bearings or rolling elements (17) on a guide (18), enabling the forward and backward movement of the whole vacuum body (2) and the pivoting of the

same in order to adapt to the loading mouthpiece (3') of the tank (3).

4. Device for collecting dust when loading concrete mixer trucks according to claim 3, **characterised by** the fact that the frusto-conical body of the vacuum head (2) is provided, at the base or mouth for coupling to the mouthpiece (3') of the tank (3), with a perimetral and cushioned piece (11) supported on channels (12) established at the rear part of the tank (3) for preventing the external outflow of the concrete.
5. Device for collecting dust when loading concrete mixer trucks according to the preceding claims, **characterised by** the fact that the common collector (10), into which the ducts (9) and (13) flow and through which ducts the dust originated when loading the tank (3) reaches said common collector (10), extends to a container or hopper (22) provided with filters for cleaning and filtering the dust, said dust falling into a gathering collector (20); a motor-driven fan (21) is associated to said container or hopper (22) for suctioning the dust through the common collector (10).








FIG.2



INTERNATIONAL SEARCH REPORT

International application No.

PCT/ES 01/00072

A. CLASSIFICATION OF SUBJECT MATTER		
IPC7 B65G 69/18, B60P 3/16 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
IPC7 B65G, B08B, B28C, B60P		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3.707.998 A (DALRYMPLE), 02 January 1973 (02.01.73) column 1, line 57-column 3, line 30; figures	1-3
A	US 3.868.238 A (MILLS, JR et al.), 25 February 1975 (25.02.75), column 1, line 60-column 2, line 40; column 3, lines 10-33; figures 1, 2.	1,2,5
A	US 3.799.221 A (VINCENT), 26 March 1974 (26.03.74) column 2, lines 17-59; figures	1,4
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "A" document member of the same patent family		
Date of the actual completion of the international search		Date of mailing of the international search report
27 March 2001 (27.03.01)		16 May 2001 (16.05.01)
Name and mailing address of the ISA/ S.P.T.O.		Authorized officer
Facsimile No.		Telephone No.

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT
Information on patent family membersInternational Application No
PCT/ES 01/00072

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3.707.998 A	02.01.1973	NONE	
US 3.868.238 A	25.02.1975	NONE	
US 3.799.221 A	26.03.1974	NONE	

Form PCT/ISA/210 (patent family annex) (July 1992)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.